



	YSH80	YSH100
A	800	1000
B	957	1157
C	1037	1237
D	1330	1530
E	1380	1580
F	2036	2236
G	1300	1500

CONVEYOR BASIC SPECIFICATION

自动人行道基本参数

Contract No. 合同号	No. of Lifts 台数
Type of conveyor 人行步道型号	HS300-0- -H
Rated Speed 额定速度	(m/s) / (ft/min)
No. of Passengers 乘客人数	(max/hour) / (个/小时)
Size 尺寸	(m) / (ft)
Power 功率	(kW) / (HP)
Load R1 额定重量	(kg) / (lb)
Load R2 额定重量	(kg) / (lb)

REMARKS 注意事项

1. In the case of units installed parallel to each other gaps should be minimized by pushing both units together leaving a minimum gap of 10 mm.
 多条配合安装时，配合间隙不得小于 10 mm。

2. requirement to Power: 电源要求
 3XV, 3-Phase 50Hz, max voltage deviation allowed ±7%
 (3-Phase 5-Wire with separate circuit breakers and fuses)
 3XV 3相 50Hz, 电压偏差 ±7% (三相五线制)

The client hereby agrees to the specification and dimensions per drawing.
 客户特此同意规格及尺寸按图施工

Approved 审核确认
 Client 客户
 CMV by the Responsible 客户代表
 CMV by the firms 单位确认

Reconfirmation is Necessary for Later Amendments bold.
 后期修改或变更需重新确认

Client 客户
 江苏单位

Structural Arrangement 结构布置图
 扶梯土建总体布置图

Page 第 1 页
 Total 共 1 页

HANSON LIFT (SUZHOU) CO.,LTD.
 苏州汉森电梯有限公司

Date 2010/05/12

借(通)用件登记

绘图

绘校

底图总号