



| ESCALATOR BASIC SPECIFICATION<br>扶梯基本规格 |                     |                 |       |
|---|---------------------|-----------------|-------|
| Contract No.<br>合同号                     | No. of Lifts<br>数量  |                 |       |
| Type of Escalator<br>扶梯类型               | SYS30- M-YW         |                 |       |
| No. of Staircases<br>扶梯数量               | No. of Floors<br>层数 |                 |       |
| Transportation<br>运输方式                  | h = i =             |                 |       |
| Rated Speed<br>额定速度                     | (m/s)               | Step            | (m)   |
| Power<br>功率                             | (kW)                | Weight          | (kg)  |
| Level 1<br>楼层 1                         | Q1                  | Level 2<br>楼层 2 | Q2    |
| Level 3<br>楼层 3                         | Q3                  | Level 4<br>楼层 4 | Q4    |
| Step Width (mm)<br>步宽 (mm)              | 1000                | 800             | 600   |
| A                                       | 1000                | 800             | 600   |
| B                                       | 1157                | 957             | 757   |
| C                                       | 1237                | 1037            | 837   |
| D                                       | 1530                | 1330            | 1130  |
| E                                       | 1580                | 1380            | 1180  |
| F                                       | 2226                | 2036            | 1836  |
| G                                       | 16000               | 17200           | 18900 |
| N                                       | 1500                | 1300            | 1100  |

REMARKS 注意事项

- To meet specific code requirements for fire escape, the treads must be extended by 47mm for step width 1000mm.
- Permissible height see local code req. EN115, if LUG intermediate support required.
- To be the case of anti-slip panels for each floor area should be maintained by pushing 20N with footplate apply a minimum gap of 10mm between the two plates of steps.
- Requirement to Power: 400V, 3-Phase 50Hz, main voltage deviation allowed ±7%, (3-Phase 50Hz with surge deviation allowed ±7%, 300V 3-Phase 50Hz, 3-Phase 50Hz, (3-Phase 50Hz with surge deviation allowed ±7%).

The client hereby agrees to the specification and dimensions per drawing.

Approved: \_\_\_\_\_  
Accepted: \_\_\_\_\_  
Date: \_\_\_\_\_

Constructional Arrangement: \_\_\_\_\_  
Escalator Drawing No.: H820-30-M-YW-90

HAISON LIFT (SUZHOU) CO., LTD.  
苏州汉森电梯有限公司

借(通)用件登记  
绘图  
绘校  
底图总号