



规格	q	M	N
YSS80	0.0039	9.5	4.5
YSS100	0.0045	11	5

规格	q	M	N
A	800	1000	
B	957	1157	
C	1057	1257	
D	1330	1530	
E	1390	1590	
F	2036	2236	
G	1300	1500	

CONVEYOR BASIC SPECIFICATION			
自动人行道基本参数			
Contract No.	合同号	No. of Units	台数
YSS100	0.0045	11	5
Model of conveyor	HS300		-N
Speed	0.5m/s		
Width	800		
Power	957		
Load	100		
Height	100		
Load to	100		
Load to	100		

REMARKS 注意事项

1. In the case of the double drive system request, truss must be installed by client.

2. In the case of units installed parallel to each other gaps should be supported by padding both with thickness being a minimum gap of 10 mm/0.4 inch according to the series of usage.

3. 3-Phase 50Hz, max voltage deviation allowed ±7%.

规格	提升高度	驱动方式		L _a	L _b	L _c
		S1	S2			
10°	1273	2154	-	-	-	-
	2155	3388	1	7000	L-7000	-
11°	3580	4799	1	L-15000	15000	-
	4800	6000	1	7000	15000	L-22000
12°	1423	2394	-	-	-	-
	2395	3754	1	7000	L-7000	-
12°	3755	5309	1	L-15000	15000	-
	5310	6000	1	7000	15000	L-22000
12°	1572	2634	-	-	-	-
	2635	4122	1	7000	L-7000	-
12°	4123	5822	1	L-15000	15000	-
	5823	6000	1	7000	15000	L-22000

1. The client hereby agrees to the specification and dimensions per loading.

2. The client hereby agrees to the specification and dimensions per loading.

3. The client hereby agrees to the specification and dimensions per loading.

4. The client hereby agrees to the specification and dimensions per loading.

5. The client hereby agrees to the specification and dimensions per loading.

借(通)用件登记

绘图

绘技

底图号

Constructional Arrangement

苏州汉森电梯有限公司

HANSON LIFT (SUZHOU) CO., LTD.